

B. Solar Radio Emission
 B1. Daily Data at Hiraiso
 500 MHz

Hiraiso

March 2004

Single-frequency total flux observations at 500 MHz					
Flux density: $10^{-22} \text{ W m}^{-2} \text{ Hz}^{-1}$					
UT Date	00-03	03-06	06-09	21-24	Day
1	38	-	-	-	38
2	-	-	-	-	-
3	-	-	-	-	-
4	-	-	-	-	-
5	-	-	-	-	-
6	-	-	-	-	-
7	-	-	-	-	-
8	-	-	-	-	-
9	-	-	-	46	46
10	36	34	35	44	37
11	39	35	35	36	36
12	36	36	35	38	36
13	34	32	31	38	34
14	34	33	32	37	34
15	35	33	32	37	34
16	34	32	32	39	34
17	34	31	30	30	31
18	32	33	34	39	34
19	36	34	34	34	35
20	34	34	32	36	34
21	33	32	32	34	33
22	33	33	33	34	33
23	34	33	32	35	33
24	33	31	32	35	33
25	34	33	33	35	34
26	33	31	30	34	32
27	33	30	30	37	32
28	34	32	32	37	33
29	33	30	29	39	33
30	37	35	35	47	39
31	45	37	35	37	39

Note: No data is available during the following periods.
 1st 0140 - 9th 0740

A superscript * stands for being superposed on a burst.

B. Solar Radio Emission
B2.Outstanding Occurrences at Hiraiso

Hiraiso

March 2004

Single-frequency observations								
Normal observing period: 2045 - 0850 U.T. (sunrise to sunset)								
MAR. 2004	FREQ. (MHz)	TYPE	START TIME (U.T.)	TIME OF MAXIMUM (U.T.)	DUR. (MIN.)	FLUX DENSITY ($10^{-22} \text{ W m}^{-2} \text{ Hz}^{-1}$)		POLARIZATION
						PEAK	MEAN	REMARKS
10	2800	7 C	2301.0	2303.0	4.0	75	-	MR
10	500	7 C	2301.0	2302.0	4.0	305	-	SR
11	2800	1 S	0214.0	0214.0	1.0	10	-	0
11	500	8 S	0721.0	0721.0	1.0	45	-	
11	500	8 S	2311.0	2311.0	1.0	20	-	0
12	500	42 SER	0028.0	0040.0	14.0	30	-	WR
12	500	4 S/F	0234.0	0236.0	7.0	130	-	0
12	2800	3 S	0235.0	0236.0	6.0	130	-	0
12	2800	23 GRF	2329.0	2334.0	19.0	25	-	0
17	500	7 C	2322.0	2329.0	7.0	10	-	0
18	2800	1 S	0514.0	0515.0	4.0	35	-	0
21	500	8 S	0648.0	0649.0	1.0	30	-	0
28	500	7 C	0345.0	0349.0	17.0	205	-	0
29	500	8 S	0157.0	0157.0	1.0	10	-	0
29	500	8 S	0757.0	0758.0	1.0	15	-	0
29	500	8 S	2146.0	2146.0	1.0	50	-	ML
29	500	4 S/F	2226.0	2228.0	7.0	205	-	ML
29	2800	1 S	2227.0	2228.0	5.0	10	-	0
29	500	8 S	2309.0	2310.0	3.0	225	-	ML
29	500	47 GB	2321.0	2333.0	9.0	1285	-	ML
29	2800	7 C	2322.0	2329.0	11.0	35	-	0
30	500	1 S	0032.0	0034.0	3.0	15	-	WL
30	500	8 S	0047.0	0049.0	3.0	100	-	WL
30	500	7 C	0127.0	0128.0	6.0	80	-	WL
30	500	8 S	0138.0	0138.0	1.0	20	-	0
30	2800	7 C	0153.0	0158.0	5.0	50	-	0
30	500	47 GB	//////	0159.0	///	////	-	WL
30	2800	1 S	0506.0	0507.0	3.0	20	-	0
30	500	8 S	0506.0	0506.0	1.0	85	-	0
30	500	47 GB	0519.0	0526.0	8.0	590	-	ML
30	2800	7 C	0522.0	0525.0	7.0	30	-	0
30	500	8 S	0543.0	0543.0	2.0	70	-	ML
30	500	8 S	0548.0	0548.0	1.0	345	-	SL
30	500	8 S	0711.0	0711.0	1.0	25	-	WL
30	500	7 C	0733.0	0734.0	3.0	20	-	WL
30	500	8 S	0746.0	0746.0	3.0	45	-	ML
30	500	8 S	2137.0	2138.0	2.0	85	-	WL
30	500	7 C	2249.0	2305.0	26.0	280	-	0
31	2800	7 C	0012.0	0015.0	4.0	55	-	0
31	2800	1 S	0601.0	0601.0	3.0	15	-	0
31	500	8 S	0601.0	0601.0	1.0	70	-	0

